

Mercury 44



DESCRIPTION AND GENERAL PROPERTIES

Composition	Abrasive fillers - Latex - Pigment - Synthetic fibers		
Dry dimensions (mm)	Length: 150	Width: 225	Thickness: 7.5
Manufacturing process	Abrasive non woven pad		
Color	Green		
Packaging	10 pieces/bag - 10 bags/carton - 100 pieces/carton		
Complementary information	A variety of sizes and abrasive charges provide the solutions to suit all requirements		



PRODUCT BENEFITS

- Stays clean longer thanks to stop grease treatment
- Rot and rust proof

SPECIFIC ADVANTAGES



Scouring power: Standard efficiency scouring:
Abrasivity Taber K500 > 250 mg / 1000 tours



Tear resistance



Tensile strenght



ENVIRONMENTS

Not recommended for delicate surfaces

FOR BEST RESULTS AND MAINTENANCE

Instructions for use:

- Not recommended for delicate surfaces.
- Use wet for an optimal efficiency.
- Use liquidproof gloves while working in contact with water or chemicals.
- Rinse after use.

Sanitizing and sterilization:

- Can be sanitized using bleach at a concentration of 1 g/l.

REGULATION / STANDARDS

Regulation REACH

This product does neither contain a substance of concern at levels greater than 0.1%, nor a substance listed in Annex XVII according to Regulation 1907/2006 of the European Parliament and of the Council (REACH).

Applicable Regulation

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.