

Mercury 96



DESCRIPTION AND GENERAL PROPERTIES

| | | | |
|----------------------------------|--|-------------------|-----------------------|
| Composition | Abrasive fillers - Latex - Pigment - Synthetic fibers | | |
| Dry dimensions (mm) | Length: 120 | Width: 150 | Thickness: 7.5 |
| Manufacturing process | abrasive non woven pad | | |
| Color | Green | | |
| Packaging | 20 pieces/bag - 8 bags/carton - 160 pieces/carton | | |
| Complementary information | A variety of sizes and abrasive charges provide the solutions to suit all requirements | | |



PRODUCT BENEFITS

- rot and rust proof

SPECIFIC ADVANTAGES



Scouring power: Standard efficiency scouring :
Abrasivity Taber K500 > 250 mg / 1000 tours



Tear resistance



Tensile strenght



ENVIRONMENTS

Not recommended for delicate surfaces

FOR BEST RESULTS AND MAINTENANCE

Instructions for use:

- Not recommended for delicate surfaces.
- Use wet for an optimal efficiency.
- Use liquidproof gloves while working in contact with water or chemicals.
- Rinse after use.

Sanitizing and sterilization:

- Can be sanitized using bleach at a concentration of 1 g/l.

REGULATION / STANDARDS

Regulation REACH

This product does neither contain a substance of concern at levels greater than 0.1%, nor a substance listed in Annex XVII according to Regulation 1907/2006 of the European Parliament and of the Council (REACH).

Applicable Regulation

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.